

### Features

- \* Bit-rate transparency
- \* Optically isolated input and output ports to minimize system susceptibility due to connector reflections
- \* Input and output signal monitoring
- \* Front panel LCD display and status LED indicators for quick access of unit's status
- \* RS-232 or Ethernet interface for remote supervision.
- \* Options for transient suppression function
- \* Redundant dual power supply

### Applications

- \* Analog video transmission systems
- \* High speed transmission systems
- \* Components or manufacturing Sub-assembly test

### Description

**GIP Technology** C-band Erbium-Doped Fiber Amplifier Unit (TLM-CEFA-00-00-U) is designed for use in the single-channel applications. They amplify optical signals across the third or fourth telecommunication window. This series incorporates a special, unique, and flexible structure to produce maximum signal gain and saturated output power while minimizing noise figure. Through optimization of these important amplifier parameters, this module will be easily deployed into any of high-quality telecommunication platforms.



The compact rack-mounted unit serves the area size. In addition, these units also provide a user-friendly status monitoring via an LCD display, LED indicators, and various communication interfaces (RS-232 and SNMP).



#### GIP Technology Corporation

6F., No. 112, Xinmin St., Zhonghe Dist.,  
New Taipei City 235, Taiwan (R.O.C.)  
T:+886-2-8226-7855 [www.giptek.com](http://www.giptek.com)  
F:+886-2-8226-7955 [sales@giptek.com](mailto:sales@giptek.com)

## Specifications

Optical Information		Unit	Description		
			Booster	In-line	Pre
Control mode		APC			
Operating wavelength range		nm	1528~1564		
Input power range	dBm	-10 ~ +10	-20 ~ 0	-30 ~ -10	
Saturated output power <sup>*1</sup>	Max. dBm	25	25	17	
Signal gain	Max. dB	25	30	40	
Noise figure	Max. dB	5.5	5.5	5	
Polarization dependent gain	Max. dB		0.3		
Polarization mode dispersion	Max. ps		0.5		
Return loss	Min. dB		45		
Connector		SC or FC			
Electrical Information					
Operating voltage	Volt	-48VDC and 100~240 VAC			
Pump LD ON/OFF switch		Key			
Control interface		RS232 & SNMP			
Environmental Information					
Ambient temperature	°C	0 ~ 50			
Storage temperature	°C	-20 ~ 80			
Relative humidity (non-condense)	%	5 ~ 85			
Mechanical Information					
Dimension		19" and 23" 1-RU rack			

\*1. Saturated power is composed of optical signal and ASE power.